



NASA Ames Research Center

# 11- by 11- Foot Transonic Wind Tunnel Facility


The 11- by 11-Foot Transonic Wind Tunnel (11-Foot TWT) Facility is part of the Unitary Plan Wind Tunnel (UPWT) complex at NASA Ames Research Center at Moffett Field, California, where generations of commercial and military aircraft and NASA space vehicles, including the space shuttle, have been designed and tested.

The 11-Foot TWT is a closed-return, variable-density tunnel with a fixed-geometry, ventilated test section with a flexible wall nozzle. It is one of three separate test sections powered by a common drive system. A three-stage, axial-flow compressor powered by four wound-rotor, variable-speed induction motors, produces airflow.



Interchangeability of models among the UPWT test sections allows testing across a wide range of conditions.

The 11-Foot TWT has been instrumental in the development of virtually every domestically produced commercial transport and military fixed-wing airframe since the 1960s. The facility is used extensively for airframe testing and aerodynamic studies and has played a vital role in every manned space flight program, including NASA's new Orion space capsule, on which astronauts will fly to the International Space Station, the Moon, and beyond.



## Facility Benefits

- Excellent optical access supports advanced flow techniques, including pressure-sensitive paint, particle image velocimetry, oil flow interferometry, infrared thermography, and Schlieren imaging
- Model supports include a rear sting, semispan turntable, 2-D Wing, high-angle kick-sting, and a roll mechanism sting provides wings-level yaw capability
- High-pressure air at 3000 psi, with a maximum flow rate of 80-pounds per second, is digitally controlled with preheating available and over 6 million scf of storage
- A steady-state data system incorporates the latest technology in a flexible, modular configuration to satisfy the most demanding test configurations, with the capability of acquiring pitch-pause and continuous-sweep data
- On-site instrumentation measures balance loads, model position, surface pressures, temperatures, and wind tunnel conditions
- An extensive library of standard aerodynamic computations is augmented by the ability to easily add customer-defined equations; corrections include wall interference and buoyancy
- A dynamic data system acquires more than 400 channels of dynamic and transient data, including unsteady pressures, aero-acoustics, and dynamic structural loads

## Data Acquisition and Processing

Steady-State Data		
System	Channels	Sample Frequency
Analog Input	48	Up to 2000 Hz
Digital Input	16	Test dependent
Force Balances	32	Up to 3000 Hz
Pressure	2048	100 Hz
Temperature	60	10 Hz
Dynamic Data		
System	Channel	Sample Frequency
Analog	300 to 450*	Up to 204-KHz

\* Depending on dynamic sensor style

## Facility Applications

- Commercial, military, and NASA programs
- Classified capability available

*“This wind tunnel has set a new standard in test productivity and technical excellence.” —Customer comment*

## Characteristics

Test Section Dimension	11-ft high by 11-ft wide by 22-ft long
Area	121 ft <sup>2</sup>
Speed	Mach 0.20 to 1.40
Reynolds Number	0.30 to $9.6 \times 10^6$ per ft
Temperature	100 ± 20 °F
Pressure	3.0 to 32 psia
Test Gas	Air

## Instrumentation

Strain Gauge Balances
Angle-of-Attack (AOA) Accelerometers
Pressure Instrumentation
Temperature Instrumentation

## Flow Visualization

Oil Flow
IR Thermography
Pressure Sensitive Paint (PSP)
Particle Image Velocimetry
Schlieren / Shadow Graph
Background Oriented Schlieren (BOS)

## Contact Information

**Frank Kmak**  
 Wind Tunnel Division Chief  
 NASA Ames Research Center  
 Phone: (650) 604-1463  
 E-mail: Frank.J.Kmak@nasa.gov  
<http://windtunnels.arc.nasa.gov>