JSC Safety and Health Requirements	JPR No.	1700.1L
	Effective Date:	12/20/2018
	Expiration Date:	12/20/2023
	Page Number	Page 2.4-1 of 8

Chapter 2.4 Routine Inspections

2.4.1 Applicability of this chapter

You are required to follow this chapter if you work at JSC or a JSC field site. Paragraph 2.4.14 of this chapter lists the responsibilities of facility managers, managers, contractor safety representatives, the Safety and Test Operations Division, and Occupational Health.

2.4.2 Routine inspections at JSC

2.4.2.1 JSC shall have a system for routinely inspecting selected work areas monthly so as to cover the entire site quarterly. This routine inspection:

- a. Is done by employees trained in recognizing hazards and may include other employees.
- b. Follows written procedures or guidance.
- c. Results in written reports of findings.
- d. Tracks hazard elimination or control to completion.

2.4.3 Purpose of safety, fire, and health inspections and evaluations

Safety, fire, and health inspections and evaluations identify hazards in the workplace so they can be corrected.

2.4.4 Safety, fire, and health inspections and evaluations at JSC

This table lists the kinds of safety, fire, and health inspections and evaluations JSC does. Inspections shall look for safety, fire, and health hazards unless otherwise noted.

What kind?	Who does them?	How often?
Construction area self-inspections to find hazards	 Construction company managers and employees Directorate safety and health committee members 	 Weekly Monthly by directorate safety and health committee members
Regular safety, fire, and health inspections to find hazards	 Safety and Test Operations Division Occupational Health 	 Yearly, or more often if necessary

JSC Safety and Health Requirements	JPR No.	1700.1L
	Effective Date:	12/20/2018
	Expiration Date:	12/20/2023
	Page Number	Page 2.4-2 of 8

What inspections?	Who does them?	How often?
Director walkthroughs to demonstrate a safety and health commitment and maintain awareness of employee concerns	Organizational directors	As determined by the Directorate
Facility manager walk- throughs to inspect for safety, health, and fire hazards	 Facility managers are responsible for making sure their buildings are inspected Managers responsible for the work area, and employees in the work area may also participate or do separate inspections 	 Inspect a few areas monthly and cover the entire building quarterly
Special inspections and surveys to look at suspected hazards	 Safety and Test Operations Division Occupational Health 	 As requested by safety and health committees, employee representatives, or employees After an employee complaint
Unannounced inspections to find hazards	 Safety and Test Operations Division Occupational Health 	As needed
Follow-up inspections to make sure hazards are corrected	 Safety and Test Operations Division Occupational Health 	 As necessary to make sure hazards are corrected
Baseline surveys get a baseline on hazards of new and newly acquired facilities, processes, materials, or equipment	 Operational readiness inspections User readiness reviews Informal survey teams Safety, fire, and health professionals 	 Before the new or newly acquired facilities, processes, materials, and equipment are used

2.4.5 Fire risk surveys

2.4.5.1 The Safety and Test Operations Division surveys all JSC work areas and operations periodically, or when a facility is built or modified. The fire risk survey isn't intended to be an allencompassing engineering survey but will try to find obvious fire hazards with normal facility operations. The survey shall look at areas such as:

- a. Exit routes and posted facility evacuation plans.
- b. Manual and automatic fire detection systems.
- c. Manual and automatic fire suppression equipment.
- d. Heating, ventilation, and air conditioning systems, if accessible.

JSC Safety and Health Requirements	JPR No.	1700.1L
	Effective Date:	12/20/2018
	Expiration Date:	12/20/2023
	Page Number	Page 2.4-3 of 8

- e. Normal and emergency lighting systems and power systems.
- f. Separation and protection of hazardous operations and material.
- g. Elevators.
- h. The adequacy and reliability of the water supply.
- i. Fire department response.
- j. Alarm monitoring equipment.
- k. Emergency procedures to include Emergency Action Plans.
- I. Existing fire risk analysis and inspection results.
- m. Other fire safety features as deemed necessary.

NOTE: For correcting deficiencies, see Chapters 3.2, "Hazard Elimination and Control," and 3.5, "Hazard Correction Tracking."

2.4.6 Inspections of inactive work areas or equipment

- 2.4.6.1 For inactive work areas or equipment, JSC organizations shall:
- a. Inspect inactive work areas or equipment at least yearly.
- b. Hold a thorough readiness review to identify hazards and take necessary actions to correct all hazards if planning to reactivate inactive work areas or equipment.
- c. Declare equipment no longer required for the performance of a specific NASA requirement as excess. Dispose of excess property using the <u>Equipment System</u> (https://equipment.nasa.gov/).

2.4.7 Preparing for an inspection

2.4.7.1 JSC managers, whether you are doing a self-inspection or being inspected by someone else, shall:

- a. Gather and review all safety, fire, and health information, such as safety, fire, and health procedures, injury and illness records, previous inspection reports, hazard reports, and corrective action reports. Give outside inspectors the results from the last self-inspection.
- b. Decide what you will inspect. You may restrict your own inspections to only areas where your employees work. Suggest what areas to inspect to outside inspectors.
- c. Stop operations that could be hazardous to those on the inspection.
- d. Provide special passes or badges for outside inspectors if necessary. Make arrangements with the Security Branch ahead of time if needed.
- e. Provide necessary personal protective equipment to your employees who go on the inspection. Tell outside inspectors what personal protective equipment they need to bring, such as hard hats, safety shoes, or respirators, before the inspection, if possible. Provide outside inspectors with personal protective equipment unique to your work area, such as gloves or protective clothing. Everyone on the inspection shall use personal protective equipment as required.

JSC Safety and Health Requirements	JPR No.	1700.1L
	Effective Date:	12/20/2018
	Expiration Date:	12/20/2023
	Page Number	Page 2.4-4 of 8

f. Arrange for employee representatives to participate. Employee representatives aren't required, but shall be given the opportunity to participate. Employees or employee groups shall have the opportunity to choose employee representatives.

2.4.8 Inspections by individuals or small teams

- 2.4.8.1 To do a self-inspection:
- a. Find safety, fire, and health hazards by:
 - (1) Using checklists you develop or <u>checklists</u> from the Safety and Test Operations Division or Occupational Health (such as the Office Safety Checklist, NS-PA-02, or one of the General Safety Checklists, NS-PA-01-1 through NS-PA-01-33, at https://smasp.jsc.nasa.gov/ns/ns1/Checklists/Home.aspx).
 - (2) Using standards from this JPR, NASA requirements, or OSHA requirements.
 - (3) Questioning any condition you think may cause a mishap.
- b. Question employees in the work areas about safety, fire, and health matters.
- c. Keep records of your inspections, and track the hazards to closure. Records shall include at least the following information:
 - (1) What hazards you found
 - (2) When and where (building and room) you found them.
 - (3) What actions you took to correct the hazards.
 - (4) When you corrected each hazard.
- d. Correct hazards on the spot, if possible.
- e. Ask the Safety and Test Operations Division or Occupational Health for a special inspection or industrial hygiene survey for things you aren't sure of.
- f. Notify all employees of the inspection results.
- g. Correct all hazards within a reasonable amount of time, as described in Chapter 3.5.

Certified industrial hygienists, certified safety professionals, professional engineers, and other safety, fire, and health professionals are available to help you with inspections and hazard correction as needed.

2.4.9 Inspections by the Safety and Test Operations Division or Occupational Health

2.4.9.1 Safety, fire, and health inspectors are authorized to enter any work area unless hazardous operations or conditions prevent entry. JSC organizations shall cooperate with safety, fire, and health inspectors when they enter the work areas. Inspectors have the right to refuse to allow anyone to accompany them who would interfere with a fair and orderly inspection. Safety, fire, and health inspectors shall follow any special procedures for entering the work areas. The inspectors shall:

a. Review safety, fire, and health information before the inspection, or ask for it when they arrive.

JSC Safety and Health Requirements	JPR No.	1700.1L
	Effective Date:	12/20/2018
	Expiration Date:	12/20/2023
	Page Number	Page 2.4-5 of 8

- b. Bring the materials and equipment they need for the inspection, such as checklists, personal protective equipment, and monitoring equipment. They won't bring any personal protective equipment that is unique to the work area.
- c. Hold an opening conference to tell managers and employees what they plan to inspect. They may inspect an entire building or work area, or just a part of a work area.
- d. Keep records on their findings. They will note any hazards corrected on the spot and make sure inspection records reflect the corrections.
- e. Interview employees and managers in the work areas. Employees interviewed have the right to bring any hazards to the attention of the inspectors.
- f. Immediately notify the manager in charge of a work area about any condition they reasonably expect could cause death or serious injury. That manager shall correct the condition immediately or take temporary measures to protect his or her employees.
- g. Hold an exit conference to discuss the inspection results with managers and employees.
- h. Send the manager in charge and the facility manager a written report on the inspection that will include the procedures followed for the inspection and findings. Include any conditions requiring a JSC Form 1240, "JSC Notice of Safety or Health Hazard and Action Plan," as described in Chapter 3.5. Reports on safety inspections are sent within 15 days. Reports on health inspections or surveys are sent within 30 days after completion.
- i. Track open hazards in the Hazard Abatement Tracking System kept by the Safety and Test Operations Division. See Chapter 3.5 for more details.

2.4.10 Follow-up to an inspection

- 2.4.10.1 After finishing the exit conference of an inspection, managers shall:
- a. Notify all employees of the inspection results.
- b. Develop action plans to correct all hazards within a reasonable amount of time as described in Chapter 3.5.
- c. Post JSC Form 1240 after recieving the written report. Keep each form posted for at least 3 days or until the hazard is corrected.

2.4.11 Inspections by OSHA or the Nuclear Regulatory Commission (NRC) or National Institute for Occupational Safety and Health (NIOSH) surveys

2.4.11.1 When OSHA or NRC representatives come to inspect JSC work areas, or NIOSH conducts surveys, JSC shall:

- a. Allow them to enter any JSC workplaces, whether occupied by government or contractor employees, to inspect or evaluate workplace conditions. The Security Branch will handle access to secure areas.
- b. Require them to show identification, and receive any necessary security clearances.
- c. Give them:
 - (1) Safety, fire, and health information on the worksites they will visit.

JSC Safety and Health Requirements	JPR No.	1700.1L
	Effective Date:	12/20/2018
	Expiration Date:	12/20/2023
	Page Number	Page 2.4-6 of 8

- (2) Photographic support, as needed and if available.
- d. Arrange for them to interview employees during their visit.
- e. Escort them during their visits. The following persons shall escort them:
 - (1) Representatives of any contractors who work in the work area to be inspected or surveyed.
 - (2) A representative from Occupational Health for NIOSH visits and OSHA visits involving health issues.
 - (3) A representative of the Safety and Test Operations Division for OSHA visits; a representative of the Safety and Test Operations Division may also escort NIOSH visitors.
 - (4) A representative from the Radiation Safety Office for NRC, NIOSH, or OSHA visits involving radiation issues.
 - (5) A manager or employee representative from the work area to be inspected.
- f. Keep OSHA and NIOSH reports on civil service employee areas at the Safety and Test Operations Division or Occupational Health.
- g. Notify NASA Headquarters Safety and Mission Assurance, the Chief Health and Medical Officer, and the Designated Agency Safety and Health Official of any impending inspections or investigations, and send the results of the inspection or survey to NASA Headquarters Safety and Mission Assurance.

2.4.12 OSHA inspections or NIOSH surveys of contractor areas

2.4.12.1 You shall provide the following to the Safety and Test Operations Division and Occupational Health within 10 working days after you get the OSHA or NIOSH report:

- a. A copy of the report
- b. A summary of any findings.
- c. A summary of actions you will take to correct the findings.

2.4.13 For more information on safety and health inspections

- a. 29 CFR 1910, "Occupational Safety and Health Standards, General Industry"
- b. 29 CFR 1926, "Occupational Safety and Health Standards, Construction Industry"
- c. 29 CFR 1960, "Basic Program Elements for Federal Employee Occupational Safety and Health Programs and Related Matters"

2.4.14 Responsibilities for routine inspections

- a. As a JSC facility manager, you are responsible for:
 - (1) Making sure self-inspections are done in your building as described in paragraphs 2.4.4, 2.4.5, 2.4.6, and 2.4.7 above. This includes making sure documentation of the inspections is available.

JSC Safety and Health Requirements	JPR No.	1700.1L
	Effective Date:	12/20/2018
	Expiration Date:	12/20/2023
	Page Number	Page 2.4-7 of 8

- (2) Doing a complete safety walkthrough of your building at least once a year to inspect for safety, health, and fire hazards. You may fulfill this by accompanying Safety and Test Operations Division personnel on their annual inspections.
- (3) Making sure action is taken on all inspections as described in paragraph 2.4.10 above.
- b. As a *JSC manager*, you are responsible for:
 - (1) Making sure self-inspections are done in your work areas as described in paragraphs 2.4.4, 2.4.5, 2.4.6, and 2.4.7 above. This includes making sure documentation of the inspections is available.
 - (2) Making sure action is taken on all inspections as described in paragraph 2.4.10 above.
 - (3) Involving employees in safety and health inspections.
- c. As a *contractor safety representative*, you are responsible for helping with contractor or NASA safety and health inspections as necessary.
- d. The Safety and Test Operations Division and Occupational Health are responsible for:
 - (1) Having qualified safety, fire, and health inspectors.
 - (2) Making sure safety and health inspectors have enough documented training and experience in finding, evaluating, and correcting hazards.
 - (3) Noting health issues during safety inspections and reporting them to Occupational Health.
 - (4) Noting safety issues during health inspections and reporting them to the Safety and Test Operations Division.
 - (5) Notifying NASA Headquarters, Office of Safety and Mission Assurance and Office of the Chief Health and Medical Officer of OSHA inspections or investigations or NIOSH surveys of JSC or contractor operations.
 - (6) Making sure audits, reviews, and assessments by NASA Headquarters, Office of Safety and Mission Assurance, are supported as described in NPR 8705.6, "Safety and Mission Assurance Audits, Reviews, and Assessments."
 - (7) Making sure audits, reviews, and assessments by NASA Headquarters, Office of the Chief Health and Medical Officer, are supported as described in Chapter 7 of NPR 1800.1.

2.4.15 Safety and health records and documentation for routine inspections

- a. Center-level records The Safety and Test Operations Division and Occupational Health shall keep records of their inspections and external inspections, and track findings in the Hazard Abatement Tracking System.
- b. Organizational-level documentation As a facility manager or manager, keep documentation of your inspections and make sure the inspections are recorded in the Building Inspection Tracking System or equivalent system for your organization. Inspection documentation shall include:
 - (1) Date and time of the inspection.

JSC Safety and Health Requirements	JPR No.	1700.1L
	Effective Date:	12/20/2018
	Expiration Date:	12/20/2023
	Page Number	Page 2.4-8 of 8

- (2) Areas or rooms inspected.
- (3) A list of participants.
- (4) Findings and actions taken. You may document the findings and actions in a tracking system or database.
- c. Organizational-level documentation JSC Form 1240 posted in work areas to inform employees of hazards.

NOTE: See Appendix F, Attachment 1.1A for details on records and documentation required by this chapter.

2.4.16 Measurement

JSC measures routine inspections by whether all work areas are inspected at least quarterly.